

Band Reject Notch Type Mobile Duplexer

25 Watt Continuous UHF Band

Model : CSG 2440

PARAMETERS	SPECIFICATIONS
Frequency Range	350 - 520 MHz
Frequency Sub bands	350-400 / 400-450 / 450-470 / 470-500 / 500 - 520 MHz
Frequency Separation	5.0 MHz
Insertion Loss	≤1.2 dB
Isolation	≥75 dB
Return Loss	≥18 dB
Connectors	BNC-Female or Customised
Power Rating	25 Watt
Operating Temperature	-30 ⁰ C to +60 ⁰ C
Dimensions Approx.(H x W x D)	32 x 155 x 120 mm
Weight (Approx.)	550 gm



WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT



Band Reject Notch Type Mobile Duplexer 50 Watt Continuous UHF Band CSG 2440 NX

PARAMETERS	SPECIFICATIONS
Frequency Range	400 ~ 500 MHz
Frequency Separation	5 / 10 MHz
Insertion Loss	≤ 1.2 dB
Isolation	≥ 75 dB
Return Loss	≥ 18 dB
Connectors	N-Female
Power Rating	50 Watt
Dimensions Approx.(HxWxD)	32 x 155 x 220 mm
Weight (Aapprox.)	1.20 kg
Operating Temperature	-25 ^o C ~ +60 ^o C



WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT
