



Band Reject Notch Type Mobile Duplexer 25 Watt Continuous VHF Band Model : CSG 2150

PARAMETERS	SPECIFICATIONS
Frequency Range	136 - 174 MHz
Frequency Sub bands	136 – 148 / 148 – 157 / 157 – 174 MHz
Frequency Separation	5.0 MHz
Insertion Loss	≤ 1.2 dB
Isolation	≥ 75 dB
Return Loss	≥ 18 dB
Connectors	UHF-Female or Customized
Power Rating	25 Watt
Operating Temperature	-30 ⁰ C to +60 ⁰ C
Dimensions Approx.(H x W x D)	32 x 155 x 138 mm
Weight (Approx.)	600 gm



WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT



Band Reject Notch Type Mobile Duplexer 50 Watt Continuous VHF Band CSG 2150 NX

PARAMETERS	SPECIFICATIONS
Frequency Range	136 ~ 174 MHz
Frequency Separation	4.0 MHz
Insertion Loss	≤ 1.2 dB
Isolation	≥ 75 dB
Return Loss	≥ 18 dB
Connectors	N-Female
Power Rating	50 Watt
Dimensions Approx.(H x W x D)	32 x 155 x 198 mm
Weight (Approx.)	1.0 kg



WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT